

# Amazing output. Intelligent automation.

Fiery® EC12, driving the FUJIFILM Revoria Press™ EC1100, delivers outstanding performance, intelligent automation, and exceptional image quality.

## Built-in print intelligence

- Maximize printer throughput with built-in Fiery JobExpert™ that will analyze print jobs and dynamically choose the optimal print settings.
- Increase efficiency with automation benefits from the built-in, browser-based Fiery JobFlow™ Base.

## Outstanding output quality

- Fiery Edge<sup>™</sup> profiles deliver stunning color with the smoothest color blends, maximum shadow details, and superb image definition.
- Built-in Fiery Preflight provides basic preflight checks to help spot file problems before printing.
- Add the optional Fiery Graphic Arts Pro Package for advanced spot color management, correcting color and images on the fly, and generating soft proofs.
- Ensure consistent, predictable output in an end-to end Adobe® workflow with Adobe PDF Print Engine rendering technology.
- Harness the productivity and output advantages of 1,200 x 1,200 dpi x 10-bit rendering.

## Differentiate with personalization

 Fiery FreeForm<sup>™</sup> Create, an included application, allows you to quickly and simply create personalised jobs for print production. Add variable elements such as text, images, or barcodes with just a few clicks.

# A unified print room

- Manage all your Fiery Driven<sup>™</sup> printers from Fiery Command WorkStation to centralize job management.
- Integrate your print production workflow with management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation.
- Easily perform complex document preparation using the included Fiery Impose and Fiery JobMaster<sup>™</sup>.



## Fiery EC12 specifications

#### Fiery Driven<sup>™</sup> engines

- FUJIFILM Revoria Press EC1100
- Supports all engine finishing

#### Hardware and platform

- Fiery® FS500 Pro software
- Intel<sup>®</sup> Core<sup>™</sup> i5-8500 Processor
- SSD boot drive for OS and Fiery software + 1 TB HDD
- 8 GB RAM
- Fiery QuickTouch™ software
- USB 3.0 ports: 2 rear ports, 3 on Fiery QuickTouch panel. USB 2.0: 4 rear ports.
- Microsoft® Windows® 10 IoT Enterprise 2019 LTSC
- Fiery Installer Builder

#### Color and imaging

- Fiery Edge<sup>™</sup> color profiles
- Fiery Ultra Smooth Gradients (1,200 x 1,200 dpi x 10-bit rendering)
- Fiery ColorWise® color management technology
- Integrated with engine inline sensor for calibration and profiling
- Fiery Spot-On™
- PANTONE® Color Enabled
- Fiery Calibrator
- Composite overprint
- Image smoothing
- Image enhance
- Fiery Image Enhance Visual Editor
- Text and graphics enhancement: color text and graphics enhancement, trailing edge compensation, positive text growth, black text and graphics anti-aliasing, text/graphics sharpness, stroke thickening for graphics

#### Performance

- SmartRIP
- Spool-RIP-Print
- Strict ordered printing
- Print Time Estimation

#### Adobe interpreter support

- Adobe® PDF Print Engine® 5.5
- CPSI version 3020

#### Productivity and workflow

- Fiery Command WorkStation®
- Fiery JobExpert<sup>™</sup>
- Fiery Impose
- Fiery JobMaster (includes 5-year subscription)
- Fiery Paper Catalog (integrated with FUJIFILM Media Library Manager)
- Fiery JobFlow<sup>™</sup> Base
- Fiery Preflight
- Fiery Hot Folders/Virtual Printers
- · Fiery drivers for Linux, Windows, Mac®, and PCL
- Fierv WebTools™
- Fiery VUE
- Fiery server presets
- Fiery Go (Android<sup>™</sup> and iOS)
- Booklet Maker
- GUI enabled
- Set Page Device mapping
- Fierv Custom Crease
- Fiery IQ: Dashboard, Insight, Notify, Go

#### Variable data printing

- Fiery FreeForm<sup>™</sup> Create
- Supported file formats: Fiery FreeForm Plus, PPML v3.o, PDF/VT-1 and 2, Creo VPS
- VDP Record and Set Level Finishing, VDP Record Range Printing, Define Record Length, VDP Resource Manager, VDP Raster Preview, VDP imposition

### File format support

- Adobe<sup>®</sup> PostScript<sup>®</sup> Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; Optimized PDF and PS; Enhanced PCL6/PCL5
- JPEG, EPS, TIFF (via Hot Folders)
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pps, ppsx, pub (via Hot

#### Integration

- Fiery JDF v1.8
- Fiery API
- MIS and Web-to-Print integration ready
- Prepress workflow integration (FUJIFILM XMF Workflow, Agfa® Apogee, SCREEN EQUIOS, Heidelberg® Prinect, Kodak® PRINERGY)

#### Security

- Secure Erase, Security profiles, Security Audit Log
- FIPS 140-2 compliant data encryption
- ISO/IEC 15408 & IEEE Std 2600 (Common Criteria) compliant <sup>2</sup>
- Option to use a customer hardened Windows OS image to meet security compliance requirements
- Port blocking, IP filtering, 802.1X authentication, IPsec encryption, HTTPs with TLS 1.3 support
- Enhanced certificate management
- Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates
- Authentication/Accounting

## Networking/Connectivity

TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication

#### EMI/EMC

FCC and ISED-ICES-003 (US & Canada); EN 55032: 2015/BS 55032:2015; CE (EU)/UKCA (UK) Marks; RCM (AS/NZS) CISPR 32: 2013; CCC-China, KC - Korea; BSMI-Taiwan

 CB Scheme – IEC 62368-1: 2018; CE-Mark (EU)/UKCA-Mark (UK); UL/CSA C.22.2 No. 62368-1: 2019 (TUV-NRTL); T-Mark EN IEC 62368-1:2020 +A11; Argentina, CCC China, BSMI-Taiwan; Oman, Kuwait, South Africa: UAE - RoHS

- Auto-switching: 100–240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 5 Amps @240 VAC
- Maximum power usage: 350 W
- Typical power usage: 100 W

#### Dimensions/Weight

- Height: 527.05 mm (20.75"); Width: 234.95 mm (9.25"); Depth: 463.55 mm (18.25")
- Weight: 16.5 kg (36.5 lbs)

#### Optional Fiery software and hardware

- Fiery Graphic Arts Pro Package 3,5
  - Fiery Preflight Pro, Fiery Spot Pro, Fiery ImageViewer, Fiery Postflight, Fiery Control Bar
- Fiery JobFlow<sup>3</sup>
- Fiery Compose 3,5
- Fiery Color Profiler Suite 4 w/ES-3000 spectrophotometer
- ES-6000 spectrophotometer
- Fiery disk drive security kit
- Adobe Acrobat® Pro Kit Fiery IQ Manage
- Fiery NX Station GL

- <sup>1</sup> Updated with enhancements and service leases on an ongoing basis
- <sup>2</sup> With proper configuration by end customer or service provide
- 3 Free 30-day trial available
- <sup>4</sup> Free trial in demo mode
- <sup>5</sup> Available as a 5-year subscription

**FUJIFILM Corporation Authorized Distributor** 

global.fujifilm.com



6453 Kaiser Drive Fremont, CA 94555

www.fiery.com

The product specifications, appearance and other details in this brochure are subject to change without notice for improvements.

Trademarks •FUJIFILM and FUJIFILM logo are registered trademarks or trademarks of FUJIFILM Corporation. •Revoria, Revoria logo and Revoria Press are registered trademarks or trademarks of FUJIFILM Business Innovation Corp.

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with Ferry, LLC products and services. ColorGuard, ColorRight, Command WorkStation, ColorWise, Flery, the Fiery logo, Fiery Compose, Fiery Driven, the Fiery Driven logo, Fiery Edge, Fiery Essential, Fiery Hyperall, Fiery Impose, Fiery