

Redefine efficiency and maximise production

Produce more high-value, complex jobs with outstanding image quality in less time with Fiery[®] IC-317, driving the Konica Minolta AccurioPress C4080/C4070/C84hc/C74hc.

Achieve optimal efficiency and effectiveness

- Handle heavy workloads with ease, plus get jobs out the door faster and more efficiently by connecting all your Fiery servers to Fiery Command WorkStation[®] to centralise job management.
- Increase your production by reducing setup time and cutting waste with Fiery JobExpert[™]. This breakthrough technology analyses incoming PDF and PostScript files and dynamically chooses the optimal Fiery print settings.
- Use Fiery Print Scheduler to visually schedule jobs within a 24-hour window to best align with daily production demands, equipment availability, and customer delivery deadlines.

Impress with superior, high-quality output

- Deliver outstanding colour with the smoothest blends, maximum shadow details, and superb image definition from Fiery Driven[™] printers with Fiery Edge[™] — the next-generation Fiery colour profiling technology.
- Fiery colour management automation is a combination of two features working in harmony to effortlessly achieve incredible colour, even for beginners, all within Command WorkStation. Media can be calibrated and profiled in just a single step, and then zero-touch recalibration keeps colour consistent with the IQ-501.
- Produce consistent and accurate colour output with robust colour matching, image correction, and proofing tools with the optional Fiery Graphic Arts Pro Package.





IC-317 v3 specifications

Fiery Driven[™] engines

- Konica Minolta AccurioPress
 C4080/C4070/C84hc/C74hc
- Supports all engine finishing devices

Hardware and platform

- Intel[®] Core[™] i5-8500 processor
- 8 GB RAM
- 1 TB HDD, SSD boot drive for OS and Fiery software
- Fiery Installer Builder
 USB 3.0 ports: 3 front, 2 rear; USB 2.0 ports: 4 rear
- Microsoft[®] Windows[®] 10 IoT Enterprise 2021 LTSC
- Fiery FS600 Pro software
- Fiery QuickTouch software

Performance

- SmartRIP
- Spool-RIP-print simultaneously
- Scan-RIP-print simultaneously
- Strict ordered printing

Colour and imaging

- Fiery Edge[™] colour profiles
 Fiery ColorWise[®] colour
- management technology • Fierv Spot-On™
- PANTONE[®] Colour Enabled
- Fiery Calibrator
- Fiery Edge spot colour
 processing
- 1-step colour management ⁹
- Zero-touch recalibration ^{5, 6}
- Composite overprint
- Fiery Image Enhance Visual Editor

Adobe interpreter support

- Adobe PDF Print Engine® 6.0 ¹
- CPSI version 3020

Productivity and workflow

- Fiery Command WorkStation[®]
- Fiery JobExpert
- Job Groups
 Print Group
 PDF Group ⁸
- Fiery Print Scheduler
- Print Time Estimation
- Fiery JobFlow[™] Base
- Fiery Preflight
- Fiery Hot Folders/Virtual Printers
- Fiery drivers for Windows and Mac^o

- Fiery VUE
- Fiery WebTools[™]
- Fiery server presets
- Fiery Go (Android[®] and iOS)
- Booklet Maker
- Direct Mobile Printing
- Pad printing
- GUI enablement
 Fiery Finishing Designer ⁷

Variable data printing

- Fiery FreeForm[™] Create
- Supported file formats include Fiery FreeForm Plus, PPML v3.0, PDF-VT 1 and 2, Creo VPS
- VDP Record and set level finishing, VDP Record Range Printing, Define Record Length, VDP Resource Manager, VDP Raster Preview, VDP imposition

File format support

- Adobe[®] PostScript[®] Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; Optimised PostScript[®] and PDF, Enhanced PCL6/PCL5
- EPS; TIFF; and JPEG (via Hot Folders)
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, ppsx, pub (via Hot Folders)

Integration

- JDF v1.8 IDP-ICS certified
- Fierv API
- MIS and Web-to-Print integration ready
- Prepress workflow integration (Heidelberg[®] Prinect, Kodak[®] PRINERGY, Agfa[®] Apogee,

SCREEN EQUIOS)

Device management and analytics

- Fiery IQ[™]: Dashboard, Insight, Notify, Go
 - Fiery ColorGuard^{™6} (3-year
 - subscription)
 - Fiery Manage (optional)

Security

© 2023 FIERY, LLC, ALL RIGHTS RESERVED.

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- FIPS 140-2 compliant data encryption

For more information, please visit www.fiery.com

• Common Criteria compliant²

 Option to use a customer hardened Windows OS image to meet security compliance requirements Dimensions

• Height: 20.75" (527.05 mm),

Width: 9.25" (234.95 mm),

Depth: 18.25" (463.55 mm)

Weight: 36.5 lb (16.5 kg)

• IQ-501 Intelligent Quality

Konica Minolta Myiro-9

Optimiser (ICCU) support

Optional Fiery software

• Konica Minolta Myiro-1 support

support (via Color Profiler Suite

Konica Minolta

compatibility

software)

and hardware

Control Bar

Fiery JobFlow ³

Fiery Manage

.

• Fiery Graphic Arts Pro

Package^{3,6} subscription

- Includes Fiery Spot Pro, Fiery

ImageViewer, Fiery Preflight

Fiery Impose ³ subscription

Fierv Compose ³ subscription

• Fiery Color Profiler Suite 4,6

• Fiery JobMaster^{™ 3} subscription

ES-3000 spectrophotometer

ES-6000 spectrophotometer

Fiery disk drive security kit

Fiery High Security Kit v1.0

Updated with enhancements and

With proper configuration by end customer or service provider

Requires inline spectrophotometer

Integrates with IQ-501 Intelligent

Requires subscription license for Fiery Impose, Compose, or JobMaster

Requires Fiery Color Profiler Suite and

FTL Km 022.04.24 UK

Integrates with TU-510 finisher

Free 30-day trial available

Free trial in demo mode

Quality Optimise

a spectrophotometer

service releases on an ongoing basis

Adobe[®] Acrobat[®] Pro Kit

• Fiery NX Station GL / LS

Pro, Fiery Postflight, and Fiery

- Port blocking, IP filtering, 802.1X authentication, IPsec encryption
- TLS 1.3 support for encrypted communications: Fiery WebTools, Fiery JobFlow, IPP, Direct Mobile Printing
- Enhanced certificate management
- Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates

Networking/Connectivity

- TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO
- Native support for Universal Print by Microsoft
- Compliant with Mopria[®] industry standard

EMC/EMI

- FCC and ICES (US & Canada)
- CE Mark (EU)
- VCCI (Japan)
- RCM (Australia & New Zealand)
- CCC (China)
- BSMI (Taiwan)
- KC Korea
- NEMKO
- CMIM Mark (Morocco)

Safety

CB Scheme

Power

100 V

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with Fiery, LLC products and services.

ColorGuard, ColorRight, Command WorkStation, ColorWise, Fiery, the Fiery logo, Fiery Compose, Fiery Driven, the Fiery Driven logo, Fiery Edge, Fiery Essential, Fiery HyperRIP, Fiery Impose, Fiery Impress, Fiery ImageViewer, Fiery Intensify, Fiery JobExpert, Fiery JobElow, Fiery JobMaster, Fiery Prep-it, Fiery Prints, the Fiery Prints logo, Fiery TrueBrand, FreeForm, MicroPress, IQ, PrintMe, RIPChips, RIP-While-Print, Spot-On, Spot Pro, and WebTools are trademarks or registered trademarks of Fiery, LIC and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged.

• TÜV/CU Mark (Canada and US)

Auto-switching: 100–240 VAC,

Typical: 100 W, 1 Amp @ 100

V. Maximum: 350 W, 7 Amp @

7-3.5 Amps, 50/60 Hz

- TÜV/T-Mark (EU)
- CE Mark (EU)
- CCC (China)
- NEMKO N-Mark
 BSMI (Taiwan)