



Fiery® Printer Controller EB-36

Fiery FS600 Pro

Maximize productivity with smart automation tools

Pair the RICOH Pro 8400 Series with the Fiery Printer Controller EB-36 to elevate your productivity and image quality to new heights.

Deliver results at lightning speed

- The Fiery Printer Controller EB-36 enhances performance with a powerful combination of hardware and the FS600 Pro system software, so you can complete more tasks in less time.
- Boost efficiency with built-in automation capabilities. Add the optional Fiery Impose and Fiery JobMaster software for fully automated imposition and advanced document assembly.
- Centralize job management with Fiery Command WorkStation® so you can simultaneously handle multiple printers and tasks.

Produce outstanding image quality

- Use grayscale calibration to preserve and enhance shadow details, ensuring accurate matches across tonal ranges.
- Fiery ImageViewer lets you inspect jobs, adjust black curves for optimal image quality, and save settings for future use.

Ensure security in your integrated production environment

- Built on the Microsoft® Windows 10 platform, the Printer Controller EB-36 contains the latest security protections like secure printing and erase, data encryption, plus configurable backup and restore.





Fiery Driven™ engines

- RICOH Pro 8400 Series

Hardware and platform

- Intel Pentium G7400E processor
- 8 GB RAM
- 500GB SATA
- 540/256GB SSD boot drive for OS and Fiery software
- Fiery Installer Builder
- USB 3.0 ports: 3 front, 2 rear
- USB 2.0 ports: 4 rear
- Windows 10 IoT Enterprise 2021 LTSC
- Fiery FS600 Pro system software

Fiery imaging technology

- Fiery imageViewer for Black and White
- Fiery grayscale calibration
- Black custom screening
- Image smoothing

Adobe interpreter support

- Adobe PDF Print Engine 6
- CPSI version 3020

Device management and analytics

- Fiery IQ™: Dashboard, Insight, Notify, EFI Go
- Fiery Manage (optional)

Performance

- Scan-RIP-print simultaneously
- Spool-RIP-print simultaneously
- Strict ordered printing

Productivity and workflow

- Fiery Command WorkStation®
- Fiery JobExpert
- Fiery drivers for Windows and Mac® users
- Fiery WebTools™
- Booklet Maker
- Pad printing
- Fiery Hot Folders/Virtual Printers
- Fiery JobFlow Base
- Direct mobile printing
- Fiery Go (Android™ and iOS)
- Print Time Estimation
- Fiery Preflight

File format support

- Adobe® PostScript® Levels 1, 2, 3
- Adobe PDF
- PDF/X-1a, 3, and 4
- Encapsulated PostScript (EPS)
- Microsoft Office document formats: doc, docx, xls,xlsx, ppt, pptx, pub (via Hot Folders)
- JPEG, TIFF

JDF/JMF support

- JDF v1.8 IDP-ICS certified
- MIS and web-to-print integration ready
- Prepress workflow integration (Agfa® Apogee, Kodak® PRINERGY, Heidelberg® Prinect)

Variable data printing

- Fiery FreeForm™ Create
- Supported file formats include Fiery FreeForm Plus, PPML v3.0, PDF/VT-1 and 2,
- Creo VPS compatible
- Record and set level finishing support
- Optimized PostScript® and PDF
- VDP record range printing
- Define record length
- VDP Raster Preview
- VDP Resource Manager

Optional Fiery software and hardware

- Fiery ES-3000 spectrophotometer
- Fiery Impose
- Fiery Compose¹
- Fiery JobMaster™¹
- Fiery High Security Kit
- Fiery JobFlow™
- Fiery Disk Drive Security Kit
- Adobe® Acrobat® Pro 2020 Kit
- Fiery NX One Station

Security

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- FIPS 140-2 compliant data encryption
- Port blocking, IP filtering, 802.1x authentication, IPsec encryption
- Enhanced certificates management
- TLS 1.3 support for encrypted communications: Fiery
- WebTools, Fiery JobFlow, IPP, Direct Mobile Printing
- Secure printing, PostScript security, USB security
- Digitally signed software updates

Networking/Connectivity

- TCP/IP, TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP,
- SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO
- Native support for Universal Print
- Compliant with Mopria®

EMC

- FCC (Canada & US)
- RCM (Australia and New Zealand)
- CE Mark (EU)
- KCC (Korea)
- BSMI (Taiwan)
- CCC (China)

Safety

- CB Scheme by TÜV
- UL/CSA
- CE Mark
- UK CA

Power supply and consumption

- Auto-switching: 100–240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum/typical power usage: 350 W / 125 W

Dimensions

- 9.75 in. (D) x 15.10 in. (H) x 8.0 in. (W)
- 248 mm (D) x 384 mm (H) x 20 mm (W)
- 13.0 lbs
- Weight with packaging: – 20.0 lbs

- 1 Free 30-day trial available
- 2 Free trial in demo mode



For more information, please visit www.fiery.com

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with Fiery, LLC products and services.

ColorGuard, ColorRight, Command WorkStation, ColorWise, Fiery, the Fiery logo, Fiery Compose, Fiery Driven, the Fiery Driven logo, Fiery Edge, Fiery Essential, Fiery HyperRIP, Fiery Impose, Fiery Impress, Fiery ImageViewer, Fiery Intensify, Fiery JobExpert, Fiery JobFlow, Fiery JobMaster, Fiery Prep-it, Fiery Prints, the Fiery Prints logo, Fiery TrueBrand, FreeForm, MicroPress, IQ, PrintMe, RIPChips, RIP-While-Print, Spot-On, Spot Pro, and WebTools are trademarks or registered trademarks of Fiery, LLC and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged.

© 2024 FIERY, LLC. ALL RIGHTS RESERVED.