

Xerox® EX C9200 Series Print Server Powered by Fiery®

SPECIFICATIONS

Get the high performance needed for higher value jobs with the Xerox® EX C9200 Series Print Server for the Xerox® PrimeLink® C9200 Series Printer

BOOST YOUR PRODUCTION AND PROFITS

Easily handle heavy workloads and provide faster turnaround times with the most powerful DFE for the Xerox® PrimeLink® C9200 Series Printer.

OUTSTANDING COLOR, EVERY TIME

Fiery Edge technology gets the most precise and stunning results from Fiery Driven™ printers. It achieves the best-possible gamut for both spot and process color reproduction.

With Fiery Spot-On™ and Fiery TrueBrand, you can ensure accurate spot colors on all job types — even Microsoft Office documents. Add the optional Fiery Graphic Arts Pro Package to get complete brand color control, adjust color and images on the fly, and generate soft proofs.

POWER TO THE OPERATOR

Gain complete control of how and when jobs print. Job Groups makes it easy to print a group of jobs in a specific order or group jobs together for multi-job makeready using Fiery Impose. With Fiery Print Scheduler, it's a breeze to schedule jobs to best align with daily production demands. Fiery Preflight provides basic preflight checks to help spot file problems before printing.

BUILT-IN PRINT INTELLIGENCE

Fiery JobExpert analyzes files and dynamically chooses the optimal print settings. So anyone can print jobs correctly — no expert knowledge required.

A SECURE, INTEGRATED PRODUCTION ENVIRONMENT

Ensure compliance with organizational security protocols with tools to secure the Windows operating system, hardware, network, and data, plus ensure complete access control.

The server features standard JDF connectivity, integrates with Xerox Standard Accounting and Xerox App Gallery applications, and is compatible with the Xerox Global Print Driver.

SPEED UP MAKEREADY

Easily perform complex document preparation using the intuitive Fiery Impose-Compose, and the optional Fiery JobMaster™.

TURN UP THE IMPACT WITH PERSONALIZATION

With Fiery FreeForm™ Create, you can quickly personalize existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks. Plus, the Fiery server supports industry-leading VDP formats like PDF/VT-1 and 2, PPML, VPS, and Xerox® VIPP® Language.



xerox™

FIERY DRIVEN ENGINES

- Xerox® PrimeLink® C9200 Series Printer
- Supports all engine finishing devices

HARDWARE/PLATFORM

- Fiery® FS600 Pro software
- Intel® Core™ i3-12100 Processor
- NVMe SSD boot drive for OS and Fiery software + 1 TB HDD
- 8 GB RAM
- Fiery Installer Builder
- USB media server
- Fiery QuickTouch™ software
- Five USB 3.x ports, two USB 2.0 ports
- Microsoft® Windows® 10 IoT Enterprise 2021 LTSC

FIERY COLOR TECHNOLOGY

- Fiery Edge™ color profiles
- Fiery Edge spot color processing
- Fiery Spot-On™
- Fiery TrueBrand
- PANTONE® Color Enabled
- Fiery Ultra Smooth Gradients
 - 1200 x 1200 dpi, 10-bit rendering resolution
- 1-step color management (requires Fiery Color Profiler Suite and ES-3000 spectrophotometer)
- Composite overprint
- Fiery Image Enhance Visual Editor
- Image enhance
- Image smoothing
- Calibration
 - Fiery Calibrator
 - ColorCal (standard, off the glass)
 - Fiery ES-3000 spectrophotometer (option)
 - Job-based calibration
 - Calibration Guard
- Auto-trapping
- Color text & graphics enhancement, text/graphics sharpness

ADOBE INTERPRETER SUPPORT

- CPSI version 3020
- Adobe PDF Print Engine 6.0 ¹

PERFORMANCE

- SmartRIP
- Spool-RIP-Print
- Strict ordered printing

FILE FORMAT SUPPORT

- Adobe® PostScript® Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; EPS; TIFF
- Enhanced PCL® 6/PCL 5
- Microsoft Office document formats (doc, docx, xls, xlsx, ppt, pptx, pub) via the Fiery driver or Fiery Hot Folders

VARIABLE DATA PRINTING (VDP)

- Fiery FreeForm Create
- Supported file formats:
 - Fiery FreeForm Plus
 - PPML v3.0
 - PDF/VT-1 and 2
 - Creo VPS
 - VI Compose, Xerox® VIPP® Language, Xerox Specialty Imaging/FreeFlow® VI Suite
- VDP record and set level finishing, define record length, VDP multi-up booklet, VDP Imposition

PRODUCTIVITY AND WORKFLOW

- Fiery Command WorkStation®
- Fiery JobExpert™
 - Includes exclusive settings for the Xerox® PrimeLink® C9200 Series Printer
 - Accessible from Xerox® FreeFlow® Core
- Fiery Impose-Compose
 - Integration with many third-party offline finishers
- Fiery Preflight
- Job Groups
 - Print Group
 - PDF Group ⁵
- Fiery drivers for Windows and Mac
- Fiery Essential Driver
- Integration with Xerox® Global Print Driver®
- Print Time Estimation
- Fiery Print Scheduler
- Fiery Hot Folders/Virtual Printers
- Fiery WebTools
- Fiery server presets
- Suspend on Mismatch, Force Print, Print/Process Next, and Rush Print, Sample Print, Proof Print
- Fiery VUE
- Fiery Go (Android and iOS)
- Booklet Maker
- Pad printing
- Visual image shift
- Direct mobile printing
- Copy numbering
- Standard support for XLS media
- Paper Catalog
- Automatic two-sided printing
- Cover selection
- N-up
- Watermarks
- Banner sheets
- Output tray selection
- Fiery Custom Crease

NETWORKING/CONNECTIVITY

- TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO (single sign-on)
- Native support for Universal Print by Microsoft®
- Compliant with Mopria® industry standard
- Single and Dual TCP/IP Connectivity for Integration with Xerox Extensible Interface Platform® (EIP)

SECURITY FEATURES

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- Trusted platform module (TPM)
- Secure Boot
- OS drive encryption (requires Fiery High Security Kit)
- FIPS 140-2 compliant data encryption. Common Criteria compliant ³
- Option to use a customer hardened Windows OS image to meet security compliance requirements
- Port blocking, IP filtering, 802.1X authentication, IPsec encryption
- TLS 1.3 support for encrypted communications: Fiery WebTools, IPP, Direct Mobile Printing
- Enhanced certificate management
- Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates

DIMENSIONS/WEIGHT

- Dimensions: 20.75" (527.05 mm) H x 9.25" (234.95 mm) W x 18.25" (463.55 mm) D
- Weight: 36.5 lb (16.5 kg)

POWER

- Auto-switching: 100–240 VAC, 7-3.5 Amps, 50/60 Hz
- Typical: 100 W, 1 Amp @ 100 V. Maximum: 350 W, 7 Amp @ 100 V

EMI/EMC

- FCC and ICES-003 (US and Canada)
- CE Mark - EN 62368-1:2014 + A11:2017 (EU)
- RCM Mark (Australia and New Zealand)
- UK CA Mark (UK)

SAFETY

- CB Scheme – 62368-1, 3rd Edition
- CU-Mark (US and Canada)
- T-Mark (EU)
- UK CA Mark (UK)

INTEGRATION

- Fiery JDF v1.8
- Fiery API
- Xerox® FreeFlow® Vision Software, Xerox® FreeFlow® Core
- Xerox® Standard Accounting
- MIS and web-to-print integration ready
- Prepress workflow integration (Agfa® Apogee, Kodak® Prinergy, Heidelberg® Prinect, SCREEN EQUIOS)

FIERY OPTIONS

- Fiery Graphic Arts Pro Package ²
 - Fiery Preflight Pro, Fiery Spot Pro, Fiery ImageViewer, Fiery Postflight, Fiery Control Bar
- Fiery JobMaster™ ²
- Fiery Color Profiler Suite⁴ with Fiery ES-3000 spectrophotometer
- Fiery NX Station GL (Keyboard, monitor, mouse and stand)
- Fiery Hub Kit (Dual IP)
- Fiery disk drive security kit
- Fiery High Security Kit (enables OS drive encryption)
- Adobe® Acrobat® Pro Kit
- Fiery Manage ²
- Fiery ColorGuard ²
- Fiery ES-6000 spectrophotometer

¹ Updated with enhancements and service releases on an ongoing basis

² Free 30-day trial available

³ With proper configuration by the end customer or service provider

⁴ Free trial in demo mode

⁵ Requires Fiery Impose, Compose, or JobMaster

For more information on the Xerox® EX C9200 Series Print Server Powered by Fiery® for the Xerox® PrimeLink® C9200 Series Printer, please contact your Xerox representative. Call 1-800-ASK-XEROX or visit us online at www.xerox.com.