



Fiery® IC-323

Fiery FS600 Pro

Redefining performance and quality

Deliver unmatched speed and exceptional quality to maximise profitability with Fiery® IC-323, driving the Konica Minolta AccurioPress C14010/C14010S/C12010/12010S.

Unmatched speed and efficiency

- Boost your production capacity with Intelligent HyperRIP™, optimising file processing to help print service providers meet tight deadlines and handle higher volumes of shorter runs with ease.
- Save time and reduce labour costs with Fiery JobFlow™ Base by automating repetitive prepress tasks. Simplify workflows, minimise errors, and seamlessly submit jobs from Fiery Command WorkStation® to deliver exceptional results with confidence.

Exceptional colour precision

- Fiery colour management automation is a combination of two features working in harmony to effortlessly achieve incredible colour, even for beginners, all within Command WorkStation. Media can be calibrated and profiled in just a single step, and then zero-touch recalibration keeps colour consistent with the IQ-601.
- Use Fiery Edge™ — the next generation colour profiling technology — for stunning colour with the smoothest colour blends, maximum shadow details, and superb image definition.
- Minimise waste, reprints, and rejected jobs with Fiery ColorGuard™ — a cloud-based colour verification solution — to track colour quality and integrates with the IQ-601.

Smarter prepress, superior results

- Produce the most accurate brand colours, correct images on the fly, and generate soft proofs with the included Fiery Graphic Arts Pro Package.
- Use Fiery JobMaster-Impose to automate document imposition and perform complex job preparation.
- Reduce setup time with Fiery JobExpert™ that can analyse the print jobs and automatically selects the optimal print settings for you.





IC-323 specifications

Fiery Driven™ engines

- Konica Minolta AccurioPress C14010/C12010
- Konica Minolta AccurioPress C14010S/C12010S with white toner⁹
- Supports all engine finishing devices

Hardware and platform

- Intel® Xeon® Silver 4310 2.1GHz Processor
- 32 GB RAM
- SSD boot drive for OS & Fiery software + 2 x 2 TB HDD
- USB 3.0: 2 rear ports, 3 on Fiery QuickTouch™ panel
- Microsoft Windows® 10 IoT Enterprise 2021 LTSC
- Fiery Installer Builder
- Fiery FS600 Pro system software
- Fiery QuickTouch software

Performance

- Fiery HyperRIP™ (8 RIPs)
 - Intelligent HyperRIP
- SmartRIP
- Scan-RIP-print simultaneously
- Spool-RIP-print simultaneously
- Strict ordered printing

Colour and imaging

- Fiery Edge™ colour profiles
- Fiery Graphic Arts Pro Package⁵ (5-year subscription included)
 - Fiery Spot Pro, Fiery ImageViewer, Fiery Preflight Pro, Fiery Postflight, and Fiery Control Bar
- Fiery Color Profiler Suite⁵ (1-year SMSA included)
- Fiery ColorWise® colour management technology
- PANTONE® Colour Enabled
- Fiery Calibrator
- Fiery Edge spot colour processing
- 1-step colour management⁸
- Zero-touch recalibration^{4,5}
- Composite overprint
- Fiery Image Enhance Visual Editor
- Fiery TrueBrand

Adobe interpreter support

- Adobe® PDF Print Engine® 6.0¹
- CPSI version 3020

Productivity and workflow

- Fiery Command WorkStation®
- Fiery JobExpert
- Fiery JobMaster™-Impose
- Job Groups
 - Print Group
 - PDF Group⁷
- Paper Catalog
- Fiery Print Scheduler
- Print Time Estimation
- Fiery JobFlow™ Base
- Fiery Hot Folders/Virtual Printers
- Fiery drivers for Windows and Mac®
- Fiery WebTools™
- Fiery server presets
- Fiery Go (Android™ and iOS)
- Booklet Maker
- GUI enablement
- Pad printing
- Direct Mobile Printing
- Fiery Finishing Designer⁶

Variable data printing

- Fiery FreeForm™ Create
- Supported file formats: Fiery FreeForm Plus, PPML v3.0, PDF/VT-1 and 2, Creo VPS
- VDP Record and Set Level Finishing, VDP Record Range Printing, Define Record Length, VDP Resource Manager, VDP Raster Preview, VDP imposition

File format support

- Adobe® PostScript® Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; Optimised PostScript® and PDF, Enhanced PCL6/PCL5
- EPS; TIFF; and JPEG (via Hot Folders)
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, ppsx, pub (via Hot Folders)

JDF/JMF support

- Fiery JDF v1.8
- Fiery API
- MIS and Web-to-Print integration ready
- Prepress workflow integration (Heidelberg® Prinect, Kodak® PRINERGY, Agfa® Apogee, SCREEN EQUIOS)

Security

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- FIPS 140-2 compliant data encryption
- Common Criteria compliant²
- Option to use a customer hardened Windows OS image to meet security compliance requirements
- Port blocking, IP filtering, 802.1X authentication, IPsec encryption
- TLS 1.3 support for encrypted communications: Fiery WebTools, Fiery JobFlow, IPP, Direct Mobile Printing
- Enhanced certificate management
- Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates

Networking/Connectivity

- TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO
- Native support for Universal Print by Microsoft
- Compliant with Mopria® industry standard

Device management and analytics

- Fiery IQ™: Dashboard, Insight, Notify, Go
 - Fiery ColorGuard⁵ (3-year subscription)
 - Fiery Manage (optional)

Safety

- EN IEC 62368-1:2020+A11:2020
- UL 62368-1:2019 (TUV NRTL)
- CAN/CSA C22.2 No. 62368-1:2019 (TUV NRTL)
- T-Mark by TUV, EN IEC 62368-1:2020+A11

EMI/EMC

- FCC Title 47, Part 15 Subpart B, Class A- NA
- ICES-003, Issue 5, August 2012, Class A- NA
- EN 55032:2015 + A11:2020 (EU) Class A
- EN61000-3-2: 2019
- EN610003-3: 2013+A1:2019
- EN 55035: 2017 + A11:2020
- EN62311: 2008

Country compliance marks

- United Kingdom (UK CA Mark)
- Australia and New Zealand (RCM Mark)
- US (FCC)
- Canada (ICES-003)
- Europe (CE Mark)
- China (CCC)
- Korea (KC)
- Taiwan (BSMI)
- Morocco
- Japan (VCCI)
- Scandanavia (Nemko EMC CoC)

Power

- Auto-switching: 100–240 VAC, 10-5 Amps, 60-50 Hz.
- Typical: 200 W, 2 Amp @ 100 V. Maximum: 600 W, 6 Amp @ 100 V

Dimensions/weight

- Height: 20.75" (527.05 mm), Width: 9.25" (234.95 mm), Depth: 22.5" (571.5 mm)
- Weight: 48 lb (21.77 kg)

Konica Minolta compatibility

- IQ-601 Intelligent Quality Optimiser (ICCU) support
- Konica Minolta Myrio-1 support
- Konica Minolta Myrio-9 support (via Color Profiler Suite software)

Optional Fiery software and hardware

- Fiery JobFlow™³
- UK-118 5-Colour Option Kit
- ES-3000 spectrophotometer
- ES-6000 spectrophotometer
- Fiery disk drive security kit
- Fiery High Security Kit v1.0
- Adobe® Acrobat® Pro Kit
- Fiery Manage
- Fiery NX Station GL / LS

¹ Updated with enhancements and service releases on an ongoing basis

² With proper configuration by end customer or service provider

³ Free 30-day trial available

⁴ Requires inline spectrophotometer

⁵ Integrates with IQ-601 Intelligent Quality Optimiser

⁶ Integrates with TU-510 finisher

⁷ Requires subscription license for Fiery Impose, Compose, or JobMaster

⁸ Requires spectrophotometer

⁹ Requires UK-118 5-Colour Option Kit



For more information, please visit www.fiery.com

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with Fiery, LLC products and services.

ColorGuard, ColorRight, Command WorkStation, Fiery, the Fiery logo, Fiery Compose, Fiery Driven, the Fiery Driven logo, Fiery Edge, Fiery Essential, Fiery HyperRIP, Fiery Impose, Fiery Impress, Fiery ImageViewer, Fiery Intensify, Fiery JobExpert, Fiery JobFlow, Fiery JobMaster, Fiery Prep-it, Fiery Prints, the Fiery Prints logo, Fiery TrueBrand, FreeForm, Fiery IQ, PrintMe, RIPChips, RIP-White-Print, Spot-On, Spot Pro, WebTools, are trademarks or registered trademarks of Fiery, LLC and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged.