

High performance with maximum productivity

Fiery Printing System 50 maximises the full power of the Kyocera TASKalfa Pro 15000c, allowing you to keep more work in-house, reduce costs, and optimise production efficiency.

Print at high speed at all times

 The highest productivity and consistent quality helps keep your cost low with no slowdowns even for demanding variable data printing tasks — perfect for government, university and corporate in-plants or CRDs.

Get unparalleled colour quality

- Fiery Edge technology gets the most precise and stunning results from Fiery Driven[™] printers. It achieves the best-possible gamut for both spot and process colour reproduction, plus superb image definition.
- With Fiery Spot-On[™] and Fiery TrueBrand, you can ensure accurate spot colours on all job types even Microsoft Office documents.

Take the guesswork out of production

- Visual, easy-to-use job management and job assembly tools such as Fiery Command WorkStation, Impose, Compose, and JobMaster help get your jobs done fast.
- Maximise printer throughput with built-in Fiery JobExpert[™] that will analyse print jobs and dynamically chooses the optimal print settings.
- Automate job preparation steps in prepress workflows to produce ready-to-print files with the browser-based, built-in Fiery JobFlow[™] Base.

See the power of personalisation

 Fiery FreeForm[™] Create, an included application, allows you to quickly and simply create personalised jobs for print production. Add variable elements such as text, images, or barcodes with just a few clicks. Plus, the Fiery server supports all major VDP formats.







Fiery Printing System 50 v2.0 specifications

Fiery Driven[™] printer

• Kyocera TASKalfa Pro 15000c

Hardware and platform

- Intel[®] Core[™] i5-12500 processor
 NVMe SSD boot drive for OS and
- Fiery software + 1 TB HDD SATA

 16 GB RAM
- Five USB 3.x ports, two USB 2.0 ports
- Microsoft[®] Windows[®] 10 IoT Enterprise 2021 LTSC
- Fiery FS600 Pro software
- Fiery QuickTouch software
- Fiery Installer Builder

Performance

- SmartRIP
- Spool-RIP-print simultaneouslyStrict ordered printing

Colour and imaging

- Fiery Edge[™] colour profiles
- Fiery Spot-On[™]
- PANTONE[®] Color Enabled
- Fiery Calibrator
- Fiery Edge spot color processing
- Composite overprint
- Fiery Image Enhance Visual Editor
- Fiery TrueBrand
- Image smoothing

Adobe interpreter support

- Adobe PDF Print Engine[®] 6.0¹
- CPSI version 3020

Productivity and workflow

- Fierv Command WorkStation®
- Fiery JobExpert
- Fiery Smart Estimator
- Job Groups
 Print Group
 PDF Group ⁵
- PDF uroup
 Paper Catalog
- Paper Latalog
 Cierry Drivet Celeadyler
- Fiery Print SchedulerPrint Time Estimation
- Print Time Estimation
 Fierv JobFlow[™] Base
- Fiery Preflight
- Fiery Hot Folders/Virtual Printers
- Fiery drivers for Windows and Mac[®]
- Fiery VUE
- Fiery WebTools™
- Fiery server presets
- Fiery Go (Android[™] and iOS)
- Booklet Maker
- Visual image shift
- Direct Mobile Printing
- Pad printing
- GUI enablement

Variable data printing

- Fiery FreeForm[™] Create
- Supported file formats include Fiery FreeForm Plus, PPML v3.0, PDF/VT-1 and 2, Creo VPS
- VDP Record and set level finishing, VDP Record Range Printing, Define Record Length, VDP Resource Manager, VDP Raster Preview, VDP imposition

File format support

- Adobe[®] PostScript[®] Levels 1, 2, 3; Adobe PDF; PDF/X-1a, 3, and 4; Optimized PostScript[®] and PDF, Enhanced PCL6/PCL5
- EPS; TIFF; and JPEG (via Hot Folders)
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, ppsx, pub (via Hot Folders)

Integration

- JDF v1.8 IDP-ICS certified
- Fiery API
- MIS and Web-to-Print
- integration ready
- Prepress workflow integration (Heidelberg[®] Prinect, Kodak[®] PRINERGY, Agfa[®] Apogee, SCREEN EOUIOS)

Security

- Secure Erase (NIST 800-88 compliant), Security profiles, Security Audit Log
- Trusted platform module (TPM)
- FIPS 140-2 compliant data
- encryption
- Common Criteria compliant²
 Option to use a customer
- hardened Windows OS image to meet security compliance requirements
- Port blocking, IP filtering, 802.1X
- authentication, IPsec encryptionTLS 1.3 support for encrypted communications: Fiery
- WebTools, Fiery JobFlow, IPP, Direct Mobile PrintingEnhanced certificate
- management
- Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software

updates

For more information, please visit www.fiery.com

respective owners and are hereby acknowledged. © 2025 FIERY, LLC. ALL RIGHTS RESERVED.

Device management and analytics

Dimensions

and hardware

subscription

Control Bar

Fiery JobFlow³

Fiery ES-3000

Fierv ES-6000

spectrophotometer

spectrophotometer

.

 Height: 20.75" (527.05 mm), Width: 9.25" (234.95 mm),

Depth: 18.25" (463.55 mm)

Weight: 36.5 lb (16.5 kg)

Optional Fiery software

Fiery Impose ⁴ subscription

Fiery Compose ³ subscription

Fiery JobMaster^{™ 3} subscription

Fiery Graphic Arts Pro Package ³

- Includes Fiery Spot Pro, Fiery

ImageViewer, Fiery Preflight

Fiery Color Profiler Suite⁴

Fiery disk drive security kit

Fiery High Security Kit v1.0

Adobe[®] Acrobat[®] Pro Kit

Fiery NX Station GL / LS

releases on an ongoing basis

Free 30-day trial available

Free trial in demo mode

With proper configuration by end customer or service provider

Impose, Compose, or JobMaste

Updated with enhancements and service

Requires subscription license for Fiery

FTL_Ky_002.01.25

Fiery ColorGuard

Fierv Manage

Pro, Fiery Postflight, and Fiery

- Fiery IQ[™]: Dashboard, Insight, Notify, Go
 - Fiery ColorGuard™ (optional)
 - Fiery Manage (optional)

Networking/Connectivity

- TCP/IP, Bonjour support, SNMP, Port 9100, IPP 2.0, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP authentication
- Login with SSO
- Native support for Universal Print by Microsoft
- Compliant with Mopria[®] industry standard

Safety

- EN IEC 62368-1:2020+A11:2020
- UL 62368-1:2019 (TUV NRTL)
- CAN/CSA C22.2 No. 62368-
- 1:2019 (TUV NRTL)
- T-Mark by TUV, EN IEC 62368-1:2020+A11

EMI/EMC

- FCC Title 47, Part 15 Subpart B, Class A- NA
- ICES-003, Issue 5, August 2012, Class A-NA
- EN 55032:2015 + A11:2020 (EU) Class A

Country compliance marks

• United Kingdom (UK CA Mark)

Australia and New Zealand

Canada (IECS-003/NMB-003)

Auto-switching: 100-240 VAC,

Typical: 100 W, 1 Amp @ 100

V. Maximum: 350 W, 7 Amp @

7-3.5 Amps, 50/60 Hz

• EN61000-3-2: 2019

(RCM Mark)

China (CCC)

Europe (CE Mark)

Korea (KC Mark)

Taiwan (BSMI)

Japan (VCCI)

Morocco

Power

100 V

Nothing herein should be construed as a warranty in addition to the express warranty statement provided with Fiery. LLC products and services.

ColorGuard, ColorRight, Command WorkStation, Fiery, the Fiery logo, Fiery Compose, Fiery Driven, the Fiery Driven logo, Fiery Edge, Fiery Essential, Fiery HyperRIP, Fiery Impose, Fiery Impress, Fiery ImageViewer, Fiery Intensify, Fiery JobExpert, Fiery JobFlow, Fiery JobMaster, Fiery Prep-it, Fiery Prints, the Fiery Prints logo, Fiery TrueBrand, FreeForm, Fiery IQ, PrintMe, RIPChips, RIP-While-Print, Spot-On, Spot Pro, WebTools, are trademarks or registered trademarks of Fiery, LC and/ or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their

US (FCC)

•

•

.

.

- EN610003-3: 2013+A1:2019
- EN 55035: 2017 + A11:2020
 EN62311: 2008