

# Xerox® EX C9200 Series Print Server Powered by Fiery®

SPECIFICATIONS

Get the high performance needed for higher-value jobs with the Xerox® EX C9200 Series Print Server for the Xerox® PrimeLink® C9200 Series Printer.

## **BOOST YOUR PRODUCTION AND PROFITS**

Easily handle heavy workloads and provide faster turnaround times with the most powerful Digital Front End (DFE) for the Xerox® PrimeLink® C9200 Series Printer.

## **STUNNING EVERY TIME**

Exclusive Fiery technology, including true 10-bit rendering at 1200 x 1200 dots per image (dpi) and Edge profiling, combined with our LED imaging and Xerox® HD EA toner, deliver smooth gradients, lifelike skin tones, and accurate fine-line reproduction.

With Fiery® Spot-On™ and Fiery® TrueBrand™, you can ensure accurate spot colors on all job types—even Microsoft Office documents.

## **TAKE FULL CONTROL OF YOUR PRINT ENVIRONMENT**

The Xerox® Job Progress Light provides real-time, 360-degree visibility into job status so operators can track progress in increments and respond quickly to alerts like empty trays or empty supplies. It's visible from long distances, mounts in any orientation, and uses simple USB plug-and-play power to help keep production moving smoothly.

## **BUILT-IN PRINT INTELLIGENCE**

Fiery® JobExpert™ analyzes files and dynamically chooses the optimal print settings, so anyone can print jobs correctly—no expert knowledge required.

## **A SECURE, INTEGRATED PRODUCTION ENVIRONMENT**

Ensure compliance with organizational security protocols with tools to secure the Windows operating system, hardware, network, and data, plus ensure complete access control.

The server features standard Job Definition Format (JDF) connectivity, integrates with Xerox® Standard Accounting Feature, and is compatible with the Xerox® Global Print Driver®.

## **SPEED UP MAKEREADY**

Easily perform complex document preparation using the intuitive Fiery Impose-Compose and the optional Fiery® JobMaster™.

## **TURN UP THE IMPACT WITH PERSONALIZATION**

With Fiery® FreeForm™ Create, you can quickly personalize existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks. Plus, the Fiery server supports industry-leading Variable Data Printing (VDP) formats like PDF/VT-1 and 2, Personalized Print Markup Language (PPML), Variable Print Specification (VPS), and Xerox® VIPP® Language.



**xerox**™

**FIERY DRIVEN ENGINES**

- Xerox® PrimeLink® C9200 Series Printer
- Supports all engine finishing devices

**HARDWARE/PLATFORM**

- Fiery® FS600 Pro software
- Intel® Core™ i3-12100 Processor
- NVMe SSD boot drive for OS and Fiery software + 1 TB HDD
- 16 GB RAM
- Fiery® Installer Builder
- USB media server
- Fiery® QuickTouch™ software
- Five USB 3.x ports, two USB 2.0 ports
- Microsoft® Windows® 10 IoT Enterprise 2021 LTSC

**FIERY COLOR TECHNOLOGY**

- FOGRA (Fogra Research Institute for Media Technologies) Certified
- Fiery® Edge™ color profiles
- Fiery® Edge™ spot color processing
- Fiery® Spot-On™
- Fiery® TrueBrand™
- PANTONE® Color Enabled
- Fiery® Ultra Smooth Gradients
  - 1200 x 1200 dpi, 10-bit rendering resolution
- 1-step color management (requires Fiery® Color Profiler Suite and the ES-3000 spectrophotometer)
- Composite overprint
- Fiery® Image Enhance Visual Editor
- Image enhance
- Image smoothing
- Calibration
  - Fiery® Calibrator
  - ColorCal (standard, off the glass)
  - Fiery® ES-3000 spectrophotometer (optional)
  - Job-based calibration
  - Calibration Guard
- Auto-trapping
- Color text and graphics enhancement, text/graphics sharpness

**ADOBE INTERPRETER SUPPORT**

- CPSI version 3020
- Adobe PDF Print Engine 6.0<sup>1</sup>

**PERFORMANCE**

- SmartRIP
- Spool-RIP-Print
- Strict ordered printing

**FILE FORMAT SUPPORT**

- Adobe PostScript® Levels 1, 2, 3; Adobe® PDF; PDF/X-1a, 3, and 4; EPS; TIFF
- Enhanced PCL® 6/PCL 5
- Microsoft Office document formats (doc, docx, xls, xlsx, ppt, pptx, pub) via the Fiery driver or Fiery Hot Folders

**VARIABLE DATA PRINTING (VDP)**

- Fiery® FreeForm™ Create
- Supported file formats:
  - Fiery® FreeForm Plus
  - PPML v3.0
  - PDF/VT-1 and 2
  - Creo VPS
  - VI Compose, Xerox® VIPP® Language, Xerox® FreeFlow® VI Suite/FreeFlow® VI Suite
- VDP record-and-set-level finishing, define record length, VDP multi-up booklet, VDP Imposition

**PRODUCTIVITY AND WORKFLOW**

- Xerox® Job Progress Light
- Fiery® Command WorkStation®
- Fiery® JobExpert™
  - Includes exclusive settings for the Xerox® PrimeLink® C9200 Series Printer
  - Accessible from Xerox® FreeFlow® Core
- Fiery® Impose-Compose
  - Integration with many third-party offline finishers
- Fiery® Preflight
- Job Groups
  - Print Group
  - PDF Group<sup>5</sup>
- Fiery® drivers for Windows and Mac
- Fiery® Essential Driver
- Integration with Xerox® Global Print Driver®
- Print Time Estimation
- Fiery® Print Scheduler
- Fiery® Hot Folders/Virtual Printers
- Fiery® WebTools
- Fiery® server presets
- Suspend on Mismatch, Force Print, Print/Process Next, Rush Print, Sample Print, and Proof Print
- Fiery® VUE
- Fiery® Go (Android and iOS)
- Booklet Maker
- Pad printing
- Visual image shift
- Direct mobile printing
- Copy numbering
- Standard support for XLS media
- Paper Catalog
- Automatic two-sided printing
- Cover selection
- N-up
- Watermarks
- Banner sheets
- Output tray selection
- Fiery® Custom Crease

**NETWORKING/CONNECTIVITY**

- Transmission Control Protocol (TCP)/Internet Protocol (IP) Bonjour support, SNMP (Simple Network Management Protocol), Port 9100, IPP (Internet Printing Protocol) 2.0, FTP (File Transfer Protocol), SMB (Server Message Block), WSD (Web Services for Devices), point and print, print via email (PS/PDF), IPv6 support, LDAP (Lightweight Directory Access Protocol) authentication
- Login with SSO (single sign-on)
- Native support for Universal Print by Microsoft®
- Compliant with Mopria® industry standard
- Single and Dual TCP/IP Connectivity for Integration with Xerox Extensible Interface Platform® (EIP)

**SECURITY FEATURES**

- Secure Erase (NIST (National Institute of Standards and Technology 800-88 compliant), Security profiles, Security Audit Log
- Trusted Platform Module (TPM)
- Secure Boot
- OS drive encryption (requires Fiery High Security Kit)
- FIPS (Federal Information Processing Standard) 140-2 compliant data encryption; Common Criteria compliant<sup>3</sup>
- Option to use a customer-hardened Windows OS image to meet security compliance requirements
- Port blocking, IP filtering, 802.1X authentication, IPsec encryption

- TLS (Transport Layer Security) 1.3 support for encrypted communications: Fiery® WebTools, IPP, Direct Mobile Printing
- Enhanced certificate management
- Fiery® self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates

**DIMENSIONS/WEIGHT**

- Dimensions: 20.75 in./527.05 mm (H) x 9.25 in./234.95 mm (W) x 18.25 in./463.55 mm (D)
- Weight: 36.5 lb./16.5 kg

**POWER**

- Auto-switching: 100–240 VAC, 7-3.5 Amps, 50/60 Hz
- Typical: 100 W, 1 Amp @ 100 V. Maximum: 350 W, 7 Amp @ 100 V

**EMI/EMC**

- FCC (Federal Communications Commission) and ICES (Interference-Causing Equipment Standards)-003 (US and Canada)
- CE (Conformité Européenne (European Conformity)) Mark—EN 62368-1:2014 + A11:2017 (EU)
- RCM (Regulatory Compliance Mark) (Australia and New Zealand)
- UKCA (UK Conformity Assessed) Mark (UK)

**SAFETY**

- CB Scheme—62368-1, 3<sup>rd</sup> Edition
- CU-Mark (US and Canada)
- T-Mark (EU)
- UK CA Mark (UK)

**INTEGRATION**

- Fiery® JDF v1.8
- Fiery® API
- Xerox® FreeFlow® Vision Connect Software
- Xerox® FreeFlow® Core
- Xerox® Standard Accounting Feature
- MIS and web-to-print integration ready
- Prepress workflow integration (Agfa® Apogee, Kodak® Prinergy, Heidelberg® Prinect, SCREEN EQUIOS)

**FIERY OPTIONS**

- Fiery® Graphic Arts Pro Package<sup>2</sup>
  - Fiery® Preflight Pro, Fiery® Spot Pro, Fiery® ImageViewer, Fiery® Postflight, Fiery® Control Bar
- Fiery® JobMaster™<sup>2</sup>
- Fiery® Color Profiler Suite<sup>4</sup> with Fiery® ES-3000 spectrophotometer
- Fiery® NX Station GL (Keyboard, monitor, mouse, and stand)
- Fiery® Hub Kit (Dual IP)
- Fiery® Disk Drive Security Kit
- Fiery® High Security Kit (enables OS drive encryption)
- Fiery® Manage<sup>2</sup>
- Fiery® ColorGuard™<sup>2</sup>

<sup>1</sup> Updated with enhancements and service releases on an ongoing basis

<sup>2</sup> Free 30-day trial available

<sup>3</sup> With proper configuration by the end customer or service provider

<sup>4</sup> Free trial in demo mode

<sup>5</sup> Requires Fiery Impose, Compose, or JobMaster

For more information on the Xerox® EX C9200 Series Print Server Powered by Fiery® for the Xerox® PrimeLink® C9200 Series Printer, please contact your Xerox representative. Call 1-800-ASK-XEROX or visit us online at [www.xerox.com](http://www.xerox.com).