

Elevate your profits with amazing output

Produce more high-value, complex jobs in less time with the Fiery® Color Controller E-45A for the Ricoh Pro C7200 Series.



Achieve maximum production efficiency

 Minimize repetitive tasks and touch points with workflow automation tools.

Impress with innovative print effects

- Differentiate print output with optional 5th color station toners such as white, clear, neon pink, neon yellow, and invisible red.
- Print intricate text details and ultra-thin lines with Fiery Dynamic HD Text and Graphics.

Effortlessly set up complex jobs

- Easily perform elaborate document preparation with optional advanced makeready tools.
- Increase efficiency with the automation benefits from the free, browser-based Fiery JobFlow Base software.

Integrate for greater efficiency

 Achieve business-wide workflow automation by integrating EFI[™] management information systems, popular prepress workflows and Web-to-Print systems.

Fiery Color Controller E-45A Specifications

Fiery Driven™ Engines

Ricoh Pro C7200S/C7210S/C7200e/ C7210X/C7210SX

Hardware and Platform

- Intel® Core™ i5-6500 processor, 3.2 GHz up to 3.6 GHz w/Turbo

- Windows 10 IoT Enterprise 2016 LTSB
- Fiery FS300 Pro software

File Format Support

- Adobe® Postscript® levels 1, 2, 3
- PDF/X output intent
- Encapsulated PostScript (EPS)
- Microsoft® Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Color and Imaging Technology

- In-line calibration with automated inline
- Specialty fifth color station support
- Fiery® ColorWise® color management technology
- Fiery Calibrator
- Fiery Spot-On™
- PANTONE® Approved
- Fiery Image Enhance Visual Editor
- Auto trapping
- Dynamic HD Text and Graphics
- Image smoothing

Productivity and Workflow

- Fiery Command WorkStation 6
- Fiery QuickTouch™ software
- Fiery Console
- Fiery JobFlow Base
- Fiery drivers for Windows and Mac
- Fiery WebToolsTM
- Fiery server presets
- Booklet Maker
- Fiery Hot Folders/Virtual Printers

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing (VDP)

- · Supported file formats include Fiery FreeForm v1 enhanced and v2.1, PPML 3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support, VDP record range printing, Define record length, VDP raster preview, VDP Resource Manager

JDF/JMF Support

- JDF v1.5 Integrated Digital Printing (IDP) ICS certified
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® APOGEE Prepress, Kodak® Prinergy® Workflow, Heidelberg® Prinect®)

Adobe Interpreter Support

- CPSI version 3020
- Adobe® PDF Print Engine (APPE) version 4*

Optional Fiery Software and Hardware

- TotalFlow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- TotalFlow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Package, Premium Edition)
- 5th color station hardware
- Fiery NX Station GL
- Fiery NX Station LS
- Fiery Impose**
- Fiery Compose
- Fiery Impose-Compose
- Fiery JobMaster**
- Fiery JobMaster-Impose
- Fiery JobFlow**
- Fiery Graphic Arts Package, Premium Edition**
- Fiery Color Profiler Suite***
- EFI ES-2000 spectrophotometer
- EFI ES-6000 spectrophotometer
- Fiery Navigator****
- Fiery Central
- Removable hard disk drive

Networking/Connectivity/Security

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, IPv6 support
- Secure Erase, Secure Printing, Backup and Restore, Fiery System Restore via WebTools, IPsec and Encryption
- Network protection includes 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification

EMI/EMC

• FCC-NA; ICES-003 Canada; VCCI_Japan; EN55032:2012/AC: 2013 (EU); AS/NZS CISPR 32: 2015A; EN61000-3-2: 2014; EN610003-3: 2013; EN55024:2010 (EU); CCC (China); KCC (Korea); EAC (Russia); BSMI (Taiwan)

Safety

IEC 60950-1:2005 (2nd Edition)+Am2:2013. IEC 62368-1:2014 (2nd Edition); UL 60950-1:2007 R10.14, UL 62368-1:2014; CAN/CSA C22.2 No. 60950-1:2007 +A2:2014, CAN/CSA C22.2 No. 62368-1-14; T-Mark \,EN 60950-1:2006+A2, EN 62368-1: 2014+A11; CCC (China); EAC (Russia)

Power Supply and Consumption

- Auto-switching: 100 -240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240
- Maximum power usage: 350 W
- Typical power usage: 125 W

Dimensions

- Server: 20.75" (527.05 mm) H x 9.25" (234.95 mm) W x 18.25" (463.55 mm) D
- Weight: 36.5 lb (16.5 kg)

*Updated with enhancements and service releases on an ongoing basis

- **Free 30-day trial available
- ***Free trial in demo mode ****licenses for first 3 Fiery servers are free

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.





Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Diven, the Fiery Diven logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraPus, UVTsaulCal, VUTEk, they on and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.