



Get higher productivity and image quality.

The Fiery® Color Controller E-35A for the Ricoh® Pro C7200SL makes it easy to print accurate color, be more productive, and reduce costs.



Effortlessly set up complex jobs

- Prepare jobs for printing with intuitive, optional makeready tools.
- Impose and preview VDP files using optional Fiery Impose software.

Produce consistent and accurate color

- Produce repeatable color every time with professional color management tools.
- Accurately reproduce spot colors to achieve the best match for corporate colors.

Integrate for greater efficiency

- Reduce touch points using Fiery JDF technology as a gateway to EFI™ MIS/ERP software, prepress workflows, and Web-to-Print systems.
- Improve consistency and flexibility of printed output with support for Adobe® PDF Print Engine® for a native end-to-end PDF workflow.

Fiery Color Controller E-35A Specifications

Fiery Driven™ Engines

- Ricoh Pro C7200SL

Hardware and Platform

- Intel® Pentium® G4400 processor, 3.3 GHz
- 8 GB RAM
- 500 GB SATA
- Windows 10 IoT Enterprise 2016 LTSB
- Fiery FS300 Pro software

File Format Support

- Adobe® Postscript® levels 1, 2, 3
- PDF/X output intent
- Encapsulated PostScript (EPS)
- Microsoft® Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Color and Imaging Technology

- Fiery® ColorWise® color management technology
- Fiery Calibrator
- Fiery Spot-On™
- PANTONE® Approved
- Fiery Image Enhance Visual Editor
- Auto trapping
- Dynamic HD Text and Graphics
- Image smoothing

Productivity and Workflow

- Fiery Command WorkStation 6
- Fiery QuickTouch™ software
- Fiery Console
- Fiery JobFlow Base
- Fiery drivers for Windows and Mac
- Fiery WebTools™
- Fiery server presets
- Booklet Maker
- Fiery Hot Folders/Virtual Printers
- Fiery API

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing (VDP)

- Supported file formats include Fiery FreeForm v1 enhanced and v2.1, PPML 3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support, VDP record range printing, Define record length, VDP raster preview, VDP Resource Manager

JDF/JMF Support

- JDF v1.5 Integrated Digital Printing (IDP) ICS certified
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® APOGEE Prepress, Kodak® Prinergy® Workflow, Heidelberg® Prinect®)

Adobe Interpreter Support

- CPSI version 3020
- Adobe® PDF Print Engine (APPE) version 4*

Optional Fiery Software and Hardware

- TotalFlow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- TotalFlow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Package, Premium Edition)
- Fiery NX One Station
- Fiery Impose**
- Fiery Compose
- Fiery Impose-Compose
- Fiery JobMaster**
- Fiery JobMaster-Impose
- Fiery JobFlow**
- Fiery Graphic Arts Package, Premium Edition**
- Fiery Color Profiler Suite***
- EFI ES-2000 spectrophotometer
- EFI ES-6000 spectrophotometer
- Fiery Navigator****
- Fiery Central
- Removable hard disk drive

Networking/Connectivity/Security

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, IPv6 support
- Secure Erase, Secure Printing, Backup and Restore, Fiery System Restore via WebTools, IPsec and Encryption
- Network protection includes 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification

EMI/EMC

- FCC Title 47, Part 15 Subpart B, Class A- (North America); ICES-003 (Canada); EN55032:2012/AC: 2013 (EU); CISPR 32: 2015, Class A (Australia/New Zealand); EN61000-3-2: 2014; EN610003-3: 2013; EN 55024: 2010 plus A1:2015; EAC (Russia); BSMI (Taiwan)

Safety

- IEC 60950-1:2005/AMD2:2013; UL 60950-1:2007 Ed.2 +R:14Oct2014; CSA C22.2#60950-1:2007 Ed.2+A1; CENELEC EN 60950-1:2006 +A11:A1;A12;C1;A2; EAC (Russia); BSMI (Taiwan)

Power Supply and Consumption

- Auto-switching: 100 –240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum/typical power usage: 150 W/100 W

Dimensions

- 9.75 in (248 mm) (D) x 15.10 in (384 mm) (H) x 8.0 in (203.2 mm) (W)
- Weight: 13.0 lbs (5.8 kg)
- Weight with packaging: 20.0 lbs (9.07 kg)

*Updated with enhancements and service releases on an ongoing basis
**Free 30-day trial available
***Free trial in demo mode
****licenses for first 3 Fiery servers are free

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.