

imagePASS-Y3

The Canon imagePASS-Y3 Print Controller for the imageRUNNER ADVANCE 8500 III and imageRUNNER ADVANCE 6500 III Series can deliver fast processing speed, outstanding image quality, and time-saving workflow.

Increase Productivity

Based on Fiery FS350 Pro system software, the Canon imagePASS-Y3 provides performance-boosting features designed to deliver high efficiency.

Experience powerful in-line finishing capabilities with support for the imageRUNNER ADVANCE 8500 III and 6500 III Series finishing options.

Fiery Command WorkStation® centralizes job management, allows you to drive multiple printers from one interface and to manage multiple jobs simultaneously from a Mac® or Windows® client for maximum productivity.

Deliver High-value Solutions

With imagePASS-Y3, you can cost effectively bring outsourced printing back in house.

Offer personalized printing with the powerful variable data printing (VDP) capabilities of the imagePASS-Y3. It supports all industry standard VDP formats, enabling a single, common print production workflow for all file types.

Integrate for Great Efficiency

Integrate your print production workflow with optional EFI™ management information systems, a variety of Web-to-Print systems, and many prepress workflows for end-to-end automation.

Manage Output and Control Costs

uniFLOW software (optional) can communicate with the imageRUNNER ADVANCE 8500 III/6500 III Series through the Canon imagePASS-Y3, allowing you to take advantage of the full suite of uniFLOW modules.



Fiery Driven™ Engines

- Canon imageRUNNER ADVANCE 8505i III/8595i III/8585i III/6575i III/6565i III/6555i III
- Support for all engine finishing options

Hardware and Platform

- Intel® Pentium® Processor G4400, 3.3 GHz
- 8 GB RAM
- 500 GB SATA HDD
- USB 3.0: two (2) rear ports and three (3) front on Fiery QuickTouch™ USB 2.0: four (4) rear ports.
- Windows® 10 IoT Enterprise 2016 LTSB
- Fiery Installer Builder
- Fiery FS350 Pro

File Format Support

- Adobe® PostScript® Levels 1, 2, 3
- Enhanced PCL® 6
- Adobe PDF
- PDF/X-1a, 3, and 4
- Encapsulated PostScript (EPS)
- MS Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Imaging Technology

- Fiery ImageViewer for black and white (optional)
- Black custom screening
- Soft proof

Productivity and Workflow

- Fiery Command WorkStation®
- Fiery drivers for Windows and Mac® users
- Fiery WebTools™
- Booklet-Maker
- Pad printing
- Fiery Hot Folders and Virtual Printers
- Direct mobile printing

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing

- Supported file formats include: Fiery FreeForm, PPML v3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support
- VDP record range printing
- Define record length
- VDP raster preview
- VDP Resource Manager

JDF/JMF Support

- JDF v1.6 Integrated Digital Printing (IDP) ICS certified
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa®:Apogee, Kodak® PRINERGY, Heidelberg® Prinect)

Adobe Interpreter Support

- CPSI version 3020
- Adobe PDF Print Engine 4*

Optional Fiery Software and Hardware

- X-Rite Eye-One spectrophotometer
- Fiery Impose
- Fiery Compose
- Fiery JobMaster™
- Fiery ImageViewer for Black and White
- Integrated Interface and Stand: Fiery stand, 22" display, keyboard, mouse
- Removable hard disk drive

Security

- Secure Erase
- Network protection includes: 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification
- LDAP support
- Secure Printing

Networking/Connectivity

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support

EMC

- FCC (Canada and US)
- C-TICK (Australia and New Zealand)
- CE Mark (EU)
- VCCI (Japan)
- BSMI (Taiwan)
- CCC (China)

Safety

- TÜV/CU Mark (Canada and US)
- TÜV/GS Mark (EU)
- CE Mark (EU)
- CB Scheme
- CCC (China)

Power Supply and Consumption

- Auto-switching: 100–240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum/typical power usage: 150 W/100 W

Dimensions

- 9.75" (H) x 8.0" (W) x 15.1" (D)
- 3247.65 mm (H) x 203.2 mm (W) x 383.54 mm (D)

* Updated with enhancements and service releases on an ongoing basis.

 USA.CANON.COM



Canon, imageRUNNER, and imagePASS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. EFI and Fiery are registered trademarks of Electronics for Imaging, Inc. in the U.S. and/or certain other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2019 Canon U.S.A., Inc. All rights reserved.