

Proven performance. Uncompromised quality.

Incorporate advanced color management and workflow automation with Ricoh Color Controller E-47B to produce high-quality output every time.

Process more high-value jobs faster

Meet critical customer turnaround times and increase production capacity with the E-47B, which processes jobs two times faster than the embedded E-27B.

Gain customer loyalty with superior output

Streamline job layout with the instant visual preview and advanced makeready capabilities of the optional Fiery Impose and Fiery JobMaster™. Correct color on-the-fly and reduce wasted prints with the optional Fiery Graphic Arts Pro Package.

Impress with outstanding image quality

Produce amazing color from Fiery EdgeTM — the next-generation EFI color profiling technology for Fiery DrivenTM printers. Out of the box, Fiery Edge delivers stunning color with the smoothest color blends, maximum shadow details, and superb image definition.

Print crisp hair-thin lines and fine details in text with the standard Dynamic HD Text and Graphics feature.

Turn up the impact with personalization

With Fiery FreeForm Create, you can quickly and simply personalize existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks.

Work smarter, not harder

Reduce setup time and cut waste with Fiery JobExpertTM — a built-in feature in Fiery Command WorkStation $^{\circ}$ — that automatically analyzes incoming PDF files and dynamically chooses optimal Fiery print settings.



Color Controller E-47B drives RICOH Pro C5300S/C5310S.

Color Controller E-47B specifications

Fiery Driven™ engines

- RICOH Pro C5300S/C5310S
- Supports all engine finishing devices

Hardware and platform

- Intel® Core™ i5-6500 processor,
 3.2 GHz up to 3.6 GHz Turbo
- 8 GB RAM
- 1 TB HDD
- Internal DVD-RW drive
- USB 3.0 ports: 3 front, 2 rear;
 USB 2.0 ports: 2 rear
- Microsoft[®] Windows[®] 10 IoT Enterprise 2019 LTSC
- Fiery FS400 Pro system software

Fiery color and imaging technology

- Fiery ColorWise* color management technology
- Fiery Edge[™] color profiles
- Fiery Dynamic HD Text & Graphics
- Fiery Calibrator
- Fiery Spot-On™
- PANTONE® color enabled
- Fiery Image Enhance Visual Editor
- Auto trapping
- · Image smoothing

Adobe interpreter support

- CPSI version 3020
- Adobe PDF Print Engine 5*

Performance

- SmartRIP
- Scan-RIP-print simultaneously
- Spool-RIP-print simultaneously
- Sequential Print

Productivity and workflow

- Fiery Command WorkStation®
- Fiery JobExpert[™]
- Fiery drivers for Windows and Mac[®]
- Fiery WebTools™
- Booklet Maker
- Pad printing
- Seguential Print
- Copy numbering
- Fiery Hot Folders/Virtual Printers
- Fiery JobFlow™ Base
- Direct mobile printing
- Fiery Go (Android™ and iOS)
- GUI enablement

File format support

- Adobe® PostScript® Levels 1, 2, 3
- Adobe PDF
- PDF/X-1a, 3, and 4
- Encapsulated PostScript (EPS)
- Microsoft Office document formats (via Hot Folders)

Variable data printing

- Fiery FreeForm™ Create
- Supported file formats include Fiery FreeForm Plus, PPML v3.0, PDF/VT 1 and 2, Creo VPS
- Record and set level finishing support
- VDP record range printing
- Define record length
- VDP Raster Preview

Integration

- JDF v1.7
- Fierv API
- EFI MIS and web-to-print integration ready
- Prepress workflow integration (Agfa* Apogee, Kodak* PRINERGY, Heidelberg* Prinect)

Security

- Secure Erase
- Security profiles
- User data encryption
- 802.1x advanced
 authentication methods

Port-based access controls

- USB security prevents connecting external storage
- Port blocking
- IP filtering
- IPsec network encryption
- Secure connections using HTTPs with support for TLS 1.3
- Secure Printing
- Digitally signed software updates
- Windows 10 OS security features

Networking/Connectivity

 TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, Point and print, Print via email, IPv6 support, LDAP authentication

EMC

- FCC Class A (Canada & US)
- RCM Class A (Australia & New Zealand)
- CE Mark (EU)
- VCCI Class A (Japan)
- CCC (China)
- EN55032:2012/AC:2013 Class A (FLI)
- EN55024:2010 (EU)

Safety

- TÜV/CU Mark (Canada & US)
- TÜV/T Mark (EU)
- CE Mark (EU)
- CB Scheme IEC60950-1/ IEC62368-1
- FAC (Russia)
- CCC (China)

Power supply and consumption

- Auto-switching: 100–240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum/typical power usage: 350 W/125 W

Dimensions

- Server: 20.75" (527.05 mm) H x 9.25" (234.95 mm) W x 18.25" (463.55 mm) D
- Server weight 36.5 lbs (16.5 kg)

Optional Fiery software and hardware

- TotalFlow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- TotalFlow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Pro Package*****)
- Fiery Graphic Arts Pro Package****
- Includes Fiery Spot Pro, Fiery ImageViewer, Fiery Preflight, Fiery Postflight, and Control Bar
- Fiery Color Profiler Suite**
- EFI ES-2000 spectrophotometer
- Fiery Impose***
- Fiery Compose
- Fiery JobMaster^{TM***}
- Fiery JobFlow***
- Fiery Navigator™
- EFI[™] ColorGuard[™]****
- Removable hard disk driveFiery NX Station GL
- Fiery NX Station LS
- Updated with enhancements and
- ** Free trial in demo mode
- *** Free 30-day trial available
- **** Free 30-day trial available and 1,2, 3, 4, or 5-year term license
- ***** Includes 5-year term license

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalized documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 650-357-3500 for more information.





Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder, Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, He Fiery logo, Fiery Driven, the Fiery DobMaster, Fiery Trints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inktensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pecas, Pecas Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Raddus, Remotebergord, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraVu, UV Series SO, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.