



Get higher productivity and image quality.

The Fiery® Colour Controller E-36A for the Ricoh® Pro C7200SL makes it easy to print accurate colour, be more productive, and reduce costs.



Effortlessly set up complex jobs

- Prepare jobs for printing with intuitive, optional makeready tools.
- Impose and preview VDP files using optional Fiery Impose software.
- With Fiery FreeForm™ Create, you can quickly and simply personalise existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks.

Produce consistent and accurate colour

- Produce repeatable colour every time with professional colour management tools.
- Accurately reproduce spot colours to achieve the best match for corporate colours.

Integrate for greater efficiency

- Reduce touch points using Fiery JDF technology as a gateway to EFI™ MIS/ERP software, prepress workflows, and Web-to-Print systems.
- Improve consistency and flexibility of printed output with support for Adobe® PDF Print Engine® for a native end-to-end PDF workflow.

Fiery Color Controller E-36A 1.1 Specifications

Fiery Driven™ Engines

- Ricoh Pro C7200SL

Hardware and Platform

- Intel® Pentium® G4400 processor, 3.3 GHz
- 8 GB RAM
- 500 GB SATA
- Windows 10 IoT Enterprise 2019 LTSC
- Fiery FS350 Pro software

File Format Support

- Adobe® Postscript® levels 1, 2, 3
- PDF/X output intent
- Encapsulated PostScript (EPS)
- Microsoft® Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Colour and Imaging Technology

- Fiery Calibrator
- Fiery Spot-On™
- PANTONE® Color Enabled
- Fiery Image Enhance Visual Editor
- Auto trapping
- Dynamic HD Text and Graphics
- Image smoothing

Productivity and Workflow

- Fiery Command WorkStation
- Fiery QuickTouch™ software
- Fiery Console
- Fiery JobFlow Base
- Fiery drivers for Windows and Mac
- Fiery WebTools™
- Fiery server presets
- Booklet Maker
- Fiery Hot Folders/Virtual Printers
- Fiery API

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing (VDP)

- Supported file formats include PPML 3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support, VDP record range printing, Define record length, VDP raster preview, VDP Resource Manager
- Fiery FreeForm™ Create

JDF/JMF Support

- Fiery JDF v1.6
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® APOGEE Prepress, Kodak® Prinergy® Workflow, Heidelberg® Prinect®)

Adobe Interpreter Support

- CPSI version 3020
- Adobe® PDF Print Engine (APPE) version 4*

Optional Fiery Software and Hardware

- Fiery Workflow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- Fiery Workflow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Package, Premium Edition)
- Fiery NX One Station
- Fiery Impose**
- Fiery Compose
- Fiery Impose-Compose
- Fiery JobMaster**
- Fiery JobMaster-Impose
- Fiery JobFlow**
- Fiery Graphic Arts Package, Premium Edition**
- Includes Fiery ImageViewer, Fiery Spot Pro, Fiery Preflight, Fiery Postflight, and Fiery Control Bar Builder
- Fiery Color Profiler Suite***
- EFI ES-2000 spectrophotometer
- EFI ES-6000 spectrophotometer
- Fiery Central
- Removable hard disk drive

Networking/Connectivity/Security

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, IPv6 support
- Secure Erase, Secure Printing, Backup and Restore, Fiery System Restore via WebTools, IPsec and Encryption
- Network protection includes 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification

EMI/EMC

- FCC Title 47, Part 15 Subpart B, Class A- (North America); ICES-003 (Canada); EN55032:2012/AC: 2013 (EU); CISPR 32: 2015, Class A (Australia/New Zealand); EN61000-3-2: 2014; EN610003-3: 2013; EN 55024: 2010 plus A1:2015; EAC (Russia); BSMI (Taiwan)

Safety

- IEC 60950-1:2005/AMD2:2013; UL 60950-1:2007 Ed.2 +R:14Oct2014; CSA C22.2#60950-1:2007 Ed.2+A1; CENELEC EN 60950-1:2006 +A11;A1;A12;C1;A2; EAC (Russia); BSMI (Taiwan)

Power Supply and Consumption

- Auto-switching: 100 –240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum/typical power usage: 150 W/100 W

Dimensions

- 9.75 in (248 mm) (D) x 15.10 in (384 mm) (H) x 8.0 in (203.2 mm) (W)
- Weight: 13.0 lbs (5.8 kg)
- Weight with packaging: 20.0 lbs (9.07 kg)

* Updated with enhancements and service releases on an ongoing basis

** Free 30-day trial available

*** Free trial in demo mode

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 0808 101 3484 (UK only) or +44 (0)1246 298000 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inktenzity, Inkware, Jettrion, the Jettrion logo, LapNet, Logic, Metrix, MicroPress, MiniNet, Monarch, OneFlow, Pace, Pecas, Pecas Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.