

Elevate your profits with amazing output

Produce more high-value, complex jobs in less time with the Fiery® Colour Controller E-46A for the Ricoh Pro C7200 Series.



Achieve maximum production efficiency

 Minimise repetitive tasks and touch points with workflow automation tools.

Impress with innovative print effects

- Differentiate print output with optional 5" colour station toners such as white, clear, neon pink and neon yellow.
- Print intricate text details and ultra-thin lines with Fiery Dynamic HD Text and Graphics.

Effortlessly set up complex jobs

- Easily perform elaborate document preparation with optional advanced makeready tools.
- Increase efficiency with the automation benefits from the free, browser-based Fiery JobFlow Base software.
- With Fiery FreeForm Create, you can quickly and simply personalise existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks.

Integrate for greater efficiency

 Achieve business-wide workflow automation by integrating EFI^{**} management information systems, EFI Web-to-Print, and popular prepress workflows.

Fiery Colour Controller E-46A 1.1 Specifications

Fiery Driven[™] Engines

 Ricoh Pro C7200S/C7210S/C7200SX/ C7210SX/C7200/C7210/C7200X/C7210X

Hardware and Platform

- Intel® Core® i5-6500 processor, 3.2 GHz up to 3.6 GHz w/Turbo
- 8 GB RAM
- 1 TB SATA
- Windows 10 IoT Enterprise 2019 LTSC
- Fiery FS350 Pro software

File Format Support

- Adobe[®] Postscript[®] levels 1, 2, 3
- PDF/X output intent
- Encapsulated PostScript (EPS)
- Microsoft® Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Colour and Imaging Technology

- In-line calibration with automated inline sensor
- · Specialty fifth colour station support
- Specialty colour calibration
- · Fiery Calibrator
- Fiery Spot-On[®]
- PANTONE® Color Enabled
- Fiery Image Enhance Visual Editor
- Auto trapping
- Dynamic HD Text and Graphics
- Image smoothing

Productivity and Workflow

- Fiery Command WorkStation
- Fiery QuickTouch* software
- Fiery Console
- Fiery JobFlow Base
- Fiery drivers for Windows and Mac
- Fiery WebTools*
- Fiery server presets
- Booklet Maker
- Fiery Hot Folders/Virtual Printers

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing (VDP)

- Supported file formats include PPML 3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support, VDP record range printing, Define record length, VDP raster preview, VDP Resource Manager
- Fiery FreeForm[™] Create

JDF/JMF Support

- Fiery JDF v1.6
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® APOGEE Prepress, Kodak® Prinergy® Workflow, Heidelberg® Prinect®)

Adobe Interpreter Support

- CPSI version 3020
- Adobe® PDF Print Engine (APPE) version 4*

Optional Fiery Software and Hardware

- Fiery Workflow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- Fiery Workflow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Package, Premium Edition)
- 5th colour station hardware
- Fierv NX Station GL
- Fiery NX Station LS
- Fiery Impose**
- · Fiery Compose
- Fiery Impose-Compose
- Fiery JobMaster**
- Fiery JobMaster-Impose
- Fiery JobFlow**
- Fiery Graphic Arts Package, Premium Edition**
- Includes Fiery ImageViewer, Fiery Spot Pro, Fiery Preflight, Fiery Postflight, and Fiery Control Bar Builder
- Fiery Color Profiler Suite***
- EFI ES-2000 spectrophotometer
- EFI ES-6000 spectrophotometer
- Fiery Central
- Removable hard disk drive

Networking/Connectivity/Security

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, IPv6 support
- Secure Erase, Secure Printing, Backup and Restore, Fiery System Restore via WebTools, IPsec and Encryption
- Network protection includes 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification

EMI/EMC

FCC-NA; ICES-003 Canada; VCCI_Japan; EN55032:2012/AC: 2013 (EU); AS/NZS CISPR 32: 2015A; EN61000-3-2: 2014; EN610003-3: 2013; EN55024:2010 (EU); CCC (China); KCC (Korea); EAC (Russia); BSMI (Taiwan)

Safety

IEC 60950-1:2005 (2nd Edition)+Am2:2013, IEC 62368-1:2014 (2nd Edition); UL 60950-1:2007 R10.14, UL 62368-1:2014; CAN/CSA C22.2 No. 60950-1:2007 +A2:2014, CAN/CSA C22.2 No. 62368-1-14; T-Mark \,EN 60950-1:2006+A2, EN 62368-1: 2014+A11; CCC (China); EAC (Russia)

Power Supply and Consumption

- Auto-switching: 100 –240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum power usage: 350 W
- Typical power usage: 125 W

Dimensions

- Server: 20.75" (527.05 mm) H x 9.25" (234.95 mm) W x 18.25" (463.55 mm) D
- Weight: 36.5 lb (16.5 kg)
 - *Updated with enhancements and service releases on an ongoing basis
 - **Free 30-day trial available ***Free trial in demo mode

EFI fuels success.

We develop breakthrough technologies for the manufacturing of signage, packaging, textiles, ceramic tiles, and personalised documents, with a wide range of printers, inks, digital front ends, and a comprehensive business and production workflow suite that transforms and streamlines the entire production process, increasing your competitiveness and boosting productivity. Visit www.efi.com or call 0808 101 3484 (UK only) or +44 (0)1246 298000 for more information.





Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, Auto-Cal, Auto-Count, Balance, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Digital StoreFront, DirectSmile, DocBuilder, DocBuilder, Pro, DockNet, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, FabriVU, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobMaster, Fiery Link, Fiery Navigator, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inktensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, Metrix, MicroPress, MinNet, Monarch, OneFlow, Pace, Pecas, Pecas Vision, PhotoXposure, PressVu, Printcafe, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, PrintStream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraVu, UV Series 50, VisualCal, VUTEk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.