



Elevate your profits with amazing output

Produce more high-value, complex jobs in less time with the Fiery® Color Controller E-46A for the Ricoh Pro C7200 Series.



Achieve maximum production efficiency

- Minimize repetitive tasks and touch points with workflow automation tools.

Impress with innovative print effects

- Differentiate print output with optional 5th color station toners such as white, clear, neon pink, neon yellow, and invisible red.
- Print intricate text details and ultra-thin lines with Fiery Dynamic HD Text and Graphics.

Effortlessly set up complex jobs

- Easily perform elaborate document preparation with optional advanced makeready tools.
- Increase efficiency with the automation benefits from the free, browser-based Fiery JobFlow™ Base software.
- With Fiery FreeForm™ Create, you can quickly and simply personalize existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks.

Integrate for greater efficiency

- Achieve business-wide workflow automation by integrating EFI™ management information systems, popular prepress workflows and Web-to-Print systems.

Fiery Color Controller E-46A 1.1 Specifications

Fiery Driven™ Engines

- Ricoh Pro C7200S/C7210S/C7200e/C7210X/C7210SX

Hardware and Platform

- Intel® Core™ i5-6500 processor, 3.2 GHz up to 3.6 GHz w/Turbo
- 8 GB RAM
- 1 TB SATA
- Windows 10 IoT Enterprise 2019 LTSC
- Fiery FS350 Pro software

File Format Support

- Adobe® Postscript® levels 1, 2, 3
- PDF/X output intent
- Encapsulated PostScript (EPS)
- Microsoft® Office document formats: doc, xls, ppt, pub (via Hot Folders)

Fiery Color and Imaging Technology

- In-line calibration with automated inline sensor
- Specialty fifth color station support
 - Specialty colour calibration
- Fiery Calibrator
- Fiery Spot-On™
- PANTONE® Color Enabled
- Fiery Image Enhance Visual Editor
- Auto trapping
- Dynamic HD Text and Graphics
- Image smoothing

Productivity and Workflow

- Fiery Command WorkStation
- Fiery QuickTouch™ software
- Fiery Console
- Fiery JobFlow Base
- Fiery drivers for Windows and Mac
- Fiery WebTools™
- Fiery server presets
- Booklet Maker
- Fiery Hot Folders/Virtual Printers

Performance

- SmartRIP
- Spool-RIP-print simultaneously

Variable Data Printing (VDP)

- Supported file formats include PPML 3.0, PDF/VT 1 and 2, Creo VPS compatible
- Record and set level finishing support, VDP record range printing, Define record length, VDP raster preview, VDP Resource Manager
- Fiery FreeForm™ Create

JDF/JMF Support

- Fiery JDF v1.6
- EFI MIS and Web-to-Print integration ready
- Prepress workflow integration (Agfa® APOGEE Prepress, Kodak® Prinergy® Workflow, Heidelberg® Prinect®)

Adobe Interpreter Support

- CPSI version 3020
- Adobe® PDF Print Engine (APPE) version 4*

Optional Fiery Software and Hardware

- TotalFlow basic bundle (Fiery Impose, EFI ES-2000 spectrophotometer)
- TotalFlow advanced bundle (Fiery Impose, Fiery Compose, Fiery Color Profiler Suite, EFI ES-2000 Spectrophotometer, Fiery Graphic Arts Package, Premium Edition)
- 5th color station hardware
- Fiery NX Station GL
- Fiery NX Station LS
- Fiery Impose**
- Fiery Compose
- Fiery Impose-Compose
- Fiery JobMaster**
- Fiery JobMaster-Impose
- Fiery JobFlow**
- Fiery Graphic Arts Package, Premium Edition**
 - Includes Fiery ImageViewer, Fiery Spot Pro, Fiery Preflight, Fiery Postflight, and Fiery Control Bar Builder
- Fiery Color Profiler Suite***
- EFI ES-2000 spectrophotometer
- EFI ES-6000 spectrophotometer
- Fiery Central
- Removable hard disk drive

Networking/Connectivity/Security

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, IPv6 support
- Secure Erase, Secure Printing, Backup and Restore, Fiery System Restore via WebTools, IPsec and Encryption
- Network protection includes 802.1x support, IP filtering, port blocking (filtering), SSL support (IPP/LDAP/HTTP/POP/SMTP), certificate management, self-signed certification

EMI/EMC

- FCC-NA; ICES-003 Canada ; VCCI_Japan; EN55032:2012/AC: 2013 (EU); AS/NZS CISPR 32: 2015A; EN61000-3-2: 2014; EN610003-3: 2013; EN55024:2010 (EU); CCC (China); KCC (Korea); EAC (Russia); BSMI (Taiwan)

Safety

- IEC 60950-1:2005 (2nd Edition)+Am2:2013, IEC 62368-1:2014 (2nd Edition); UL 60950-1:2007 R10.14, UL 62368-1:2014; CAN/CSA C22.2 No. 60950-1:2007 +A2:2014, CAN/CSA C22.2 No. 62368-1-14; T-Mark \,EN 60950-1:2006+A2, EN 62368-1: 2014+A11; CCC (China); EAC (Russia)

Power Supply and Consumption

- Auto-switching: 100 –240 VAC
- 50/60 Hz, 6 Amps @100 VAC, 3 Amps @240 VAC
- Maximum power usage: 350 W
- Typical power usage: 125 W

Dimensions

- Server: 20.75" (527.05 mm) H x 9.25" (234.95 mm) W x 18.25" (463.55 mm) D
- Weight: 36.5 lb (16.5 kg)

*Updated with enhancements and service releases on an ongoing basis

**Free 30-day trial available

***Free trial in demo mode

EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.